


NOROO

NOROO Paint & Coatings

PH:(+61)1300 655 853

www.noroo.com.au

sales@oxide.com.au



FLOOR COATING SYSTEM

NOROO

NOROO Paint & Coatings

Australia / New Zealand Distributor



236 Planet St Welshpool, WA Australia

PH: 1300 655 853

Emai:sales@oxide.com.au

CLEANPOXY(W) PRIMER

Cleanpoxy(W) Primer is a two-part water based epoxy resin primer. Used as primer for a water based epoxy system used with Cleanpoxy(W) Top Coat. It has low VOC with excellent adhesion properties ideal where eco-friendly requirements are needed.

Available in 16L Kit

CLEANPOXY(W) TOP COAT

Cleanpoxy(W) Top Coat is a two-part water based epoxy resin. Used as top coat for a water based epoxy system with Cleanpoxy(W) Primer. It has low VOC with excellent adhesion properties, water resistance, abrasion resistance, excellent durability and great workability with a fast dry time.

Available in 16L Kit

DNY-200 PRIMER

DNY-200 is a two-part epoxy primer designed to be used as a primer coat without thinning additives. It is especially suitable for concrete because of its excellent permeability. In particular, it enhances the strength of the concrete mortar surface and improves adhesion between the substrate and the subsequent coatings

Available in 16L Kit

DNY-200(E) PRIMER

DNY-200(E) is a two-part 100% solids epoxy primer & universal resin. It is suitable as a floor undercoat, enhancing the strength of the concrete surface due to its excellent adhesion, permeability, water resistance and chemical resistance. Reduced VOC for internal coatings.

Available in 16L Kit

CLEANPOXY 3100

Cleanpoxy 3100 is a solvent based 2-pack epoxy top coat resin product. Excellent abrasion resistance, chemical resistance, and adhesion. It is widely used as a coating for interior finishing that requires dustproofing, stain resistance or where a improved internal UV resistance is desired. Suitable for light duty traffic.

Available in 16L Kit

DHDC 6400

DHDC 6400 is a 100% solids 2-pack epoxy product, ideal as a top coat finish. It has excellent adhesion, appearance, durability and chemical resistance. Commonly used in performance epoxy flooring for warehouses, commercial applications, also ideal for use in a decorative flake coat system for residential or commercial areas.

Available in 16L Kit

ANYTHANE (POLYURETHANE)

Anythane is a clear top coat two-part solvent based polyurethane. Ideal as a top coat finish for when a smooth glossy finish is desired on a surface such as a flake floor. Anythane is tintable and offers a beautiful dry film appearance and outstanding color retention. Suitable for interior or exterior uses due to UV stability

Available in 16L Kit

YEGREENA COLORFLOOR (PRIMER & TOP COAT)

Yegreena Colorfloor is a clear two part epoxy system consisting of a primer and top coat. Specifically designed for superior metallic & pearl pigmented resin coatings. Yegreena Colorfloor offers fast drying with excellent properties of hardness, adhesion, durability, chemical resistance and dust proofness. The product forms a smooth and beautiful appearance after application, and added metallic pearls maximize the interior decorative effect. Metallic tints available in 26+ different colours.

Available in 6kg Kit (Primer) Available in 13.5kg Kit (Top Coat)

NOROO

NOROO Paint & Coatings

Epoxy Flooring Systems

Water Based

System	Product	Coats	Remarks
Prime Coat	Cleanpoxy(W) Primer	1 (40µm)	Suitable for internal enclosed areas low VOC eco-friendly
Top Coat	Cleanpoxy(W) Top Coat	1-2 (35µm - 70µm)	

Optional decorative coating effects such as spray speckle effect & flake coating

Light Duty

System	Product	Coats	Remarks
Prime Coat	DNY 200 or DNY 200(E)	1 (50µm - 100µm)	Suitable as a dust proofing option for light duty uses. Economical coverage.
Top Coat	Cleanpoxy 3100	1-2 (40µm - 80µm)	

Optional Non-slip additives compatible

Heavy Duty

System	Product	Coats	Remarks
Prime Coat	DNY 200 or DNY 200(E)	1 (50µm - 100µm)	Suitable for heavy duty industrial areas such as commercial warehouses, show rooms, kitchens, or any other high traffic areas.
Top Coat	DHDC 6400	1-2 (0.25mm - 1mm)	

Optional Non-slip additives compatible

Flake

System	Product	Coats	Remarks
Prime Coat	DNY 200 or DNY 200(E)	1 (50µm - 100µm)	Multipurpose uses residential & commercial. 35+ different flake options available.
Epoxy Coat	DHDC 6400	1 (0.25mm)	
Flake	Flake	Full or partial coverage	
Top Coat	Anythane	1-2 (40µm - 80µm)	

Metallic

System	Product	Coats	Remarks
Prime Coat	Yegreena Primers	1 (150µm)	Decorative looking finish 26+ metallic pigment colours to choose from.
Top Coat	Yegreena Top Coat	1-2 (1mm - 2mm)	

Optional top coat with Anythane for maximum protection

Guides above for coatings are recommendations only for more detailed requirements talk to your engineer or specifier